

Data sheet for three-phase Squirrel-Cage-Motors**三相异步鼠笼电动机数据表****MLFB-Ordering data:** 1TL8004-2BD23-3AA5**Motor type:**

Client order no.:

Order no.:

Offer no.:

Remarks:

U	D / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _A /I _N	T _A /T _N	T _B /T _N	
380	D	50	22	/	48.0	737	285	92.1	92.8	92.5	0.76	0.70	0.58	7	2.7	3	IE4
660	Y	50	22	/	27.5	737	285	92.1	92.8	92.5	0.76	0.70	0.58	7	2.7	3	IE4
IMB3			FS 225M		313 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Mechanical data / 机械性能数据

Sound pressure level 50Hz/60Hz (No load) 声压等级 50Hz/60Hz (空载)(dB(A))	58
Moment of inertia 转动惯量 (kgm ²)	0.83
Bearing DE NDE 轴承 DE NDE	6313 C3 6213 C3
Relubrication quantity (DE NDE) 再润滑用量 (g) (DE NDE)	20 20
Relubrication interval (DE NDE) 再润滑周期 (h) (DE NDE)	8000
Lubricants 润滑脂	2# Li Grease
Regreasing device 再润滑装置	Yes
Grease nipple 油杯	M10x1
Type of bearing 轴承类型	Fixed bearing on NDE
Condensate drainage holes 排水孔	No
External earthing terminal 外部接地	No
Vibration class 振动等级	A
Insulation 绝缘等级	155(F)
Duty type 工作方式	S1
Direction of rotation 旋转方向	Bidirectional
Frame material 机座材料	Cast iron
Data of anti condensation heating 防潮加热	No
Coating 喷漆	Yes
Color 颜色	RAL 7011
Motor protection 电机保护	A=without winding protection
Method of cooling 冷却方式	IC411 - Self ventilated, surface cooled

Terminal box / 接线盒

Terminal box position 接线盒位置	Right
Material of terminal box 接线盒材料	Steel
Type of terminal box 接线盒型号	/
Cable diameter 电缆直径 (mm)	32~36
Max. cross-sectional area 最大电缆截面积 (mm ²)	/
Main terminal thread 接线端子螺纹	6XM8
Cable gland 葛兰	1 plug+1 gland
Main cable entry 主进线孔螺纹规格	2xM50X1.5

Special design / 特殊设计**Environmental conditions / 环境条件**

Ambient temperature 环境温度(°C)	-15 ~ 40
Altitude above sea level 海拔高度 (m)	1000