



Data sheet for three-phase Asynchronous Squirrel-Cage-Motors

三相异步鼠笼电动机数据表

MLFB-Ordering data: 1TL8014-2AA43-3AA4 D24

Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

U	D / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _s /I _N	M _s /M _N	M _k /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _s /I _N	T _s /T _N	T _B /T _N	
380	D	50	30	/	54	2970	96.5	94.5	94.6	94.0	0.89	0.87	0.80	8.5	2.6	3.1	IE4
660	Y	50	30	/	31	2970	96.5	94.5	94.6	94.0	0.89	0.87	0.80	8.5	2.6	3.1	IE4
IM B3			FS 200L		284 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Mechanical data / 机械性能数据		Terminal box / 接线盒	
Sound pressure level 50Hz/60Hz (No load) 声压等级 50Hz/60Hz (空载)(dB(A))	71 /	Terminal box position 接线盒位置	Top
Moment of inertia 转动惯量 (kgm²)	0.266	Material of terminal box 接线盒材料	steel
Bearing DE NDE 轴承 DE NDE	6212 Z C3 / 6212 Z C3	Type of terminal box 接线盒型号	/
Relubrication quantity (DE NDE) 再润滑用量 (g) (DE NDE)	/ /	Cable diameter 电缆直径 (mm)	32-36
Relubrication interval (DE NDE) 再润滑周期 (h) (DE NDE)	/	Max. cross-sectional area 最大电缆截面积 (mm²)	/
Lubricants 润滑脂	/	Main terminal thread 接线端子螺纹	6XM6
Regreasing device 再润滑装置	/	Cable gland 葛兰	1 plug+1 gland
Grease nipple 油杯	no	Main cable entry 主进线孔螺纹规格	2xM50X1.5
Type of bearing 轴承类型	Fixed bearing on NDE	Special design / 特殊设计	
Condensate drainage holes 排水孔	no		
External earthing terminal 外部接地	no		
Vibration class 振动等级	A		
Insulation 绝缘等级	155(F)		
Duty type 工作方式	S1		
Direction of rotation 旋转方向	Bidirectional		
Frame material 机座材料	Cast iron		
Data of anti condensation heating 防潮加热	no		
Coating 喷漆	yes		
Color 颜色	RAL 7011		
Motor protection 电机保护	A=without winding protection		
Method of cooling 冷却方式	IC411 - Self ventilated, surface cooled		
Environmental conditions / 环境条件			
Ambient temperature 环境温度(°C)	-20 ~ 40		
Altitude above sea level 海拔高度 (m)	1000m		

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
若有技术更改，恕不另行通知！计算出的数据可能和铭牌数据有所不同！