



Data sheet for three-phase Asynchronous Squirrel-Cage-Motors

三相异步鼠笼电动机数据表

MLFB-Ordering data: 1MT8004-2BD03-3AA4

Flameproof grade: Ex db IIB T4 Gb



Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

U	D / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _s /I _N	M _s /M _N	M _k /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _s /I _N	T _s /T _N	T _B /T _N	
380	D	50	18.5	/	40.5	738	239	91.7	92.4	92.1	0.76	0.70	0.59	7	2.6	3	IE4
660	Y	50	18.5	/	23	738	239	91.7	92.4	92.1	0.76	0.70	0.59	7	2.6	3	IE4
IM B3			FS 225S		377 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Mechanical data / 机械性能数据		
Sound pressure level 50Hz/60Hz (No load) 声压等级 50Hz/60Hz (空载)(dB(A))	59	/
Moment of inertia 转动惯量 (kgm²)	0.734	
Bearing DE NDE 轴承 DE NDE	6313 C3	6313 C3
Relubrication quantity (DE NDE) 再润滑用量 (g) (DE NDE)	20g	20g
Relubrication interval (DE NDE) 再润滑周期 (h) (DE NDE)	8000h	
Lubricants 润滑脂	2# Li Grease	
Regreasing device 再润滑装置	Yes	
Grease nipple 油杯	M10x1	
Type of bearing 轴承类型	Floating bearing DE	
Condensate drainage holes 排水孔	No	
External earthing terminal 外部接地	Yes	
Vibration class 振动等级	A	
Insulation 绝缘等级	155(F)	
Duty type 工作方式	S1	
Direction of rotation 旋转方向	Bidirectional	
Frame material 机座材料	Cast iron	
Data of anti condensation heating 防潮加热	No	
Coating 喷漆	Yes	
Color 颜色	RAL 7011	
Motor protection 电机保护	A=without winding protection	
Method of cooling 冷却方式	IC411 - Self ventilated, surface cooled	

Environmental conditions / 环境条件	
Ambient temperature 环境温度(°C)	-20 ~ 40
Altitude above sea level 海拔高度 (m)	1000m

Terminal box / 接线盒	
Terminal box position 接线盒位置	Top
Material of terminal box 接线盒材料	Cast iron
Type of terminal box 接线盒型号	/
Cable diameter 电缆直径 (mm)	19~20/25~26/31~32/37~38/41~42
Hoop gland diameter 接线盒斗直径	1xφ72
Main terminal thread 接线端子螺纹	6xM8
Cable gland 葛兰	/
Max. auxiliary terminals 最大辅助端子数	/
Auxiliary cable entry 辅助进线孔	/

Special design / 特殊设计
