

**Data sheet for three-phase Asynchronous Squirrel-Cage-Motors****三相异步鼠笼电动机数据表****MLFB-Ordering data:** 1MT8004-3AA03-3AA4

Flameproof grade: Ex db IIB T4 Gb

**Motor type:**

Client order no.:

Order no.:

Offer no.:

Remarks:

U	D / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I <sub>s</sub> /I <sub>N</sub>	M <sub>s</sub> /M <sub>N</sub>	M <sub>k</sub> /M <sub>N</sub>	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I <sub>s</sub> /I <sub>N</sub>	T <sub>s</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>	
380	D	50	110	/	196	2982	352	96.0	95.9	95.1	0.89	0.88	0.82	8.5	2.1	2.4	IE4
660	Y	50	110	/	113	2982	352	96.0	95.9	95.1	0.89	0.88	0.82	8.5	2.1	2.4	IE4
IM B3			FS 315S		1090 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

**Mechanical data / 机械性能数据**

Sound pressure level 50Hz/60Hz (No load) 声压等级 50Hz/60Hz (空载)(dB(A))	77	/
Moment of inertia 转动惯量 (kgm <sup>2</sup> )	2.089	
Bearing DE   NDE 轴承 DE   NDE	6316 C3	6316 C3
Relubrication quantity (DE NDE) 再润滑用量 (g) (DE NDE)	30g	30g
Relubrication interval (DE NDE) 再润滑周期 (h) (DE NDE)	3000h	
Lubricants 润滑脂	2# Li Grease	
Regreasing device 再润滑装置	Yes	
Grease nipple 油杯	M10x1	
Type of bearing 轴承类型	Floating bearing DE	
Condensate drainage holes 排水孔	No	
External earthing terminal 外部接地	Yes	
Vibration class 振动等级	A	
Insulation 绝缘等级	155(F)	
Duty type 工作方式	S1	
Direction of rotation 旋转方向	Bidirectional	
Frame material 机座材料	Cast iron	
Data of anti condensation heating 防潮加热	No	
Coating 喷漆	Yes	
Color 颜色	RAL 7011	
Motor protection 电机保护	A=without winding protection	
Method of cooling 冷却方式	IC411 - Self ventilated, surface cooled	

**Terminal box / 接线盒**

Terminal box position 接线盒位置	Top
Material of terminal box 接线盒材料	Cast iron
Type of terminal box 接线盒型号	/
Cable diameter 电缆直径 (mm)	30~31/35~36/44~45/49~50
Hoop gland diameter 接线盒斗直径	2xφ90
Main terminal thread 接线端子螺纹	6xM16
Cable gland 葛兰	/
Max. auxiliary terminals 最大辅助端子数	/
Auxiliary cable entry 辅助进线孔	/

**Special design / 特殊设计****Environmental conditions / 环境条件**

Ambient temperature 环境温度(°C)	-20 ~ 40
Altitude above sea level 海拔高度 (m)	1000m